

## TECHNICAL SPECIFICATION DIVISION

Specification No.: RTES-115/2563 : AUTOMATIC INSULATION ANALYZER Page 1 of 8

## C3 Schedule of detailed requirement

| Item | PEA<br>Material<br>No. | Quantity | Description  |
|------|------------------------|----------|--|
| 1    | No.                    | set(s)   | Portable insulation analyzer, for field testing of insulation in electrical equipment and apparatus up to 115 kV 50 Hz in live substations e.g. power transformers, bushings etc., and for measurements and calculations of capacitance, power factor, watt loss, current, and voltage; consisting of high voltage test section and control and measuring section; with;  Output voltage : up to 12 kV, continuously adjustable  Output current : up to 200 mA  Capacitance : 0.062 uF, or better  Power supply : single-phase, 220 VAC, 50 Hz  Complete with  1. Input circuit-breaker  2. Standard protective device(s)  3. Automatic interference protection/suppression  4. Raise-lower voltage control  5. Resonating inductor for increases current output (if any)  6. Indication and pilot lamps  7. Oil test cell, in accordance with ASTM-D 924 or equivalent; with case  8. Main supply cord and plug  9. Shielded high-voltage test cable with pothead on both ends  10. Low-voltage test lead(s)  11. Safety ground leads and accessories  12. Cable hook  13. Instruction books  14. Other accessories according to manufacturer's design and auxiliary equipment not specified in these specifications, but necessary to complete the sound |
| 2    | -                      | 1 lot    | function  Spare parts for the portable insulation analyzer in item 1 (give detail)   |
| 3    | -                      | 1 lot    | Optional accessories for the portable insulation analyzer in item 1 (give detail)  |
| 4    | -<br>II                | 1 lot    | Training course for PEA's personnel including on-site training for operation and maintenance of the portable insulation analyzer in item 1.  |



## TECHNICAL SPECIFICATION DIVISION

Specification No.: RTES-115/2563 : AUTOMATIC INSULATION ANALYZER Page 2 of 8

## C3 Schedule of detailed requirement

| Item | PEA<br>Material<br>No. | Quantity   | Description                        |   |  |  |
|------|------------------------|--|------------------------------------|---|--|--|
| 5    | -                      | set(s)   | Automatic insulation analyze       | r, fully automatic, modular and portable design, suitable |  |  |
|      |                        |  | for field testing of insulation in | electrical equipment and apparatus up to 115 kV 50 Hz     |  |  |
|      |                        | in live substations e.g. power transformers, circuit break |                                    | transformers, circuit breakers, bushings etc., and for    |  |  |
|      |                        |  | measurements and calculations      | s of voltage, current, power factor, dissipation factor,  |  |  |
|      |                        |  | capacitance, inductance, and       | watt loss; consisting of high voltage test section and    |  |  |
|      |                        |  | control and measuring section,     | with:   |  |  |
|      |                        |  | Safety standards                   |   |  |  |
|      |                        |  | - EMC                              | : IEC 61326-1, or equivalent                              |  |  |
|      |                        |  | - safety                           | : IEC 61010-1, or equivalent                              |  |  |
|      |                        |  | Function                           |   |  |  |
|      |                        |  | - power transformer                | : leakage reactance                                       |  |  |
|      |                        |  |                                    | : short circuit impedance                                 |  |  |
|      |                        |  |                                    | : frequency response of stray losses (FRSL)               |  |  |
|      |                        |  |                                    | : excitation current                                      |  |  |
|      |                        |  |                                    | : winding resistance                                      |  |  |
|      |                        |  |                                    | : demagnetization   |  |  |
|      |                        |  |                                    | : dynamic load tap change                                 |  |  |
|      |                        |  |                                    | : transformer turn ratio                                  |  |  |
|      |                        |  |                                    | : dissipation factor                                      |  |  |
|      |                        |  |                                    | : insulation capacitance                                  |  |  |
|      |                        |  | - current transformer              | : ratio, burden and polarity                              |  |  |
|      |                        |  |                                    | : winding resistance                                      |  |  |
|      |                        |  |                                    | : voltage withstand                                       |  |  |
|      |                        |  |                                    | : excitation curve  |  |  |
|      |                        |  |                                    | : dissipation factor                                      |  |  |
|      |                        |  | - voltage transformer              | : ratio, burden and polarity                              |  |  |
|      |                        |  |                                    | : voltage withstand                                       |  |  |
|      |                        |  |                                    | : dissipation factor                                      |  |  |
|      |                        |  | Output voltage                     |   |  |  |
|      |                        |  | - AC voltage                       | : 0 to 2,000 V, or better                                 |  |  |
|      |                        |  |                                    |   |  |  |
|      | II                     |  |                                    |   |  |  |



## TECHNICAL SPECIFICATION DIVISION

Specification No.: RTES-115/2563 : AUTOMATIC INSULATION ANALYZER Page 3 of 8

## C3 Schedule of detailed requirement

| Item | PEA<br>Material<br>No. | Quantity |                               | Description  |
|------|------------------------|----------|-------------------------------|--|
|      |                        |          | Output current                |  |
|      |                        |          | - AC current                  | : 0 to 2,000 A, or better                              |
|      |                        |          | - DC current                  | : 0 to 100 A, or better                                |
|      |                        |          | Maximum output power          |  |
|      |                        |          | - AC output power             | : 0 to 2,500 VA, or better                             |
|      |                        |          | - DC output power             | : 0 to 1,000 VA, or better                             |
|      |                        |          | Test voltage                  |  |
|      |                        |          | - AC voltage range            | : 0 to 2,000 V, or better                              |
|      |                        |          | - AC voltage accuracy         | : $\leq$ 0.2% reading $\pm$ 0.2% full scale            |
|      |                        |          | Test current                  |  |
|      |                        |          | - AC current range            | : 0 to 800 A, or better                                |
|      |                        |          | - DC current range            | : 0 to 100 A, or better                                |
|      |                        |          | - AC current accuracy         | : $\leq 0.2\%$ reading $\pm 0.2\%$ full scale          |
|      |                        |          | - DC current accuracy         | : $\leq$ 0.2% reading $\pm$ 0.2% full scale            |
|      |                        |          | Test frequency                |  |
|      |                        |          | - AC frequency range          | : 15 Hz to 400 Hz at 0 to 250 $V_{\rm ac}$ , or better |
|      |                        |          |                               | : 45 Hz to 70 Hz at 0 to 12 kV $_{ac}$ , or better     |
|      |                        |          | Power factor                  |  |
|      |                        |          | - power factor range          | : 0 to 100 %   |
|      |                        |          | - power factor accuracy       | : $\leq 0.5\%$ reading $\pm 0.02$ %                    |
|      |                        |          | Dissipation factor            |  |
|      |                        |          | - dissipation factor range    | : 0 to 10,000 % at 300 V to 10 kV, or better           |
|      |                        |          | - dissipation factor accuracy | $: \le 0.5\%$ reading $\pm 0.02$ %                     |
|      |                        |          | Capacitance (at 50 Hz)        |  |
|      |                        |          | - capacitance range           | : 1 pF to 3 uF at 300 V to 10 kV, or better            |
|      |                        |          | - capacitance accuracy        | $0.5\%$ reading $\pm 1$ pF                             |
|      |                        |          | Inductance (at 50 Hz)         |  |
|      |                        |          | - inductance range            | : 10 H to 10 kH at 300 V to 10 kV, or better           |
|      |                        |          | - inductance accuracy         | $: \le 0.5\%$ reading $\pm 1$ mH                       |
|      |                        |          | Control and measuring section | : build in LCD display, or better                      |
|      |                        |          | PC communication interface    | : USB or Ethernet port, completed with                 |
|      | II                     |          |                               | communication cable                                    |



## TECHNICAL SPECIFICATION DIVISION

Specification No.: RTES-115/2563 : AUTOMATIC INSULATION ANALYZER Page 4 of 8

## C3 Schedule of detailed requirement

|       | PEA      |          |  |  |  |  |
|-------|----------|----------|--|--|--|--|
| Item  | Material | Quantity | Description  |  |  |  |
| Ittin | No.      | Quantity | Description  |  |  |  |
|       | 1100     |          | Operating temperature : up to 50°C, or better  |  |  |  |
|       |          |          | Power supply : single phase 230V, 50Hz   |  |  |  |
|       |          |          | Complete with:   |  |  |  |
|       |          |          | Serial interface for a accessories device such as tan delta unit                       |  |  |  |
|       |          |          | 2. Instruction and maintenance manual, English, shall be contain following             |  |  |  |
|       |          |          | information:   |  |  |  |
|       |          |          | a) Operating principle   |  |  |  |
|       |          |          | b) Operating instruction of test set and user interface software                       |  |  |  |
|       |          |          | c) Setting and adjustments   |  |  |  |
|       |          |          | d) Maintenance instructions or troubleshooting instruction                             |  |  |  |
|       |          |          | e) Part list and circuit diagram   |  |  |  |
|       |          |          | 3. High-voltage supply shielded cable, not less than 18 meters long, with connection   |  |  |  |
|       |          |          | clamp  |  |  |  |
|       |          |          | 4. Measuring shielded cables, not less than 18 meters long, with connection clamps     |  |  |  |
|       |          |          | 5. Grounding cable, not less than 6 meters long, with connection clamp and accessories |  |  |  |
|       |          |          | 6. Power supply and plug   |  |  |  |
|       |          |          | 7. Thermometer and hygrometer for measuring air temperature and humidity               |  |  |  |
|       |          |          | 8. Transport cart and carrying bag or case for the analyzer and accessories            |  |  |  |
|       |          |          | 9. Oil test cell, in accordance with ASTM D924, or equivalent with carrying case       |  |  |  |
|       |          |          | 10. Software package comprising useful function and using on computer with             |  |  |  |
|       |          |          | Windows TM operating system for analysis the data from the analyzer and marking        |  |  |  |
|       |          |          | reports.   |  |  |  |
|       |          |          | 11. Certificate of calibration   |  |  |  |
|       |          |          | 12. Switchbox  |  |  |  |
|       |          |          | 13. Other accessories according to manufacturer's design and auxiliary equipment       |  |  |  |
|       |          |          | necessary to complete the function.  |  |  |  |
| 6     | -        | 1 lot    | Spare part for the automatic insulation analyzer in item 5 (give detail)               |  |  |  |
| 7     | -        | 1 lot    | Optional accessories for the automatic insulation analyzer in item 5 (give detail)     |  |  |  |
|       | II       |          |  |  |  |  |



## TECHNICAL SPECIFICATION DIVISION

Specification No.: RTES-115/2563 : AUTOMATIC INSULATION ANALYZER Page 5 of 8

### C3 Schedule of detailed requirement

| Item | PEA<br>Material | Quantity  |   | Description  |  |  |
|------|-----------------|-----------|---|--|--|--|
|      | No.             | Quarterly |   | 2000-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1                   |  |  |
| 8    | -               | set(s)    | Automatic insulation analyzer, for                            | ally automatic, modular and portable design, suitable      |  |  |
|      |                 |           | for field testing of insulation in e                          | electrical equipment and apparatus e.g. transformer,       |  |  |
|      |                 |           | circuit breakers, current transforme                          | er, voltage transformer, protection relay, etc., and for   |  |  |
|      |                 |           | measurements and calculations of                              | voltage, current and resistance; consisting of high        |  |  |
|      |                 |           | voltage test section and control and measuring section, with: |  |  |  |
|      |                 |           | Safety standards  |  |  |  |
|      |                 |           | - EMC   | : IEC 61326-1, or equivalent                               |  |  |
|      |                 |           | - safety  | : IEC 61010-1, or equivalent                               |  |  |
|      |                 |           | Output voltage  |  |  |  |
|      |                 |           | - AC voltage  | : 0 to 2,000 V, or better                                  |  |  |
|      |                 |           | Output current  |  |  |  |
|      |                 |           | - AC current  | : 0 to 2,000 A, or better                                  |  |  |
|      |                 |           | - DC current  | : 0 to 100 A, or better                                    |  |  |
|      |                 |           | Maximum output power  |  |  |  |
|      |                 |           | - AC output power   | : 0 to 2,500 VA, or better                                 |  |  |
|      |                 |           | - DC output power   | : 0 to 1,000 VA, or better                                 |  |  |
|      |                 |           | Test voltage  |  |  |  |
|      |                 |           | - AC voltage range  | : 0 to 2,000 V, or better                                  |  |  |
|      |                 |           | - AC voltage accuracy   | : $\leq 0.2\%$ reading $\pm 0.2\%$ full scale              |  |  |
|      |                 |           | Test current  |  |  |  |
|      |                 |           | - AC current range  | : 0 to 800 A, or better                                    |  |  |
|      |                 |           | - DC current range  | : 0 to 100 A, or better                                    |  |  |
|      |                 |           | - AC current accuracy   | : $\leq 0.2\%$ reading $\pm 0.2\%$ full scale              |  |  |
|      |                 |           | - DC current accuracy   | : $\leq 0.2\%$ reading $\pm 0.2\%$ full scale              |  |  |
|      |                 |           | Test frequency  |  |  |  |
|      |                 |           | - AC frequency range  | : 15 Hz to 400 Hz at 0 to 250 $V_{\rm ac},$ or better      |  |  |
|      |                 |           | Control and measuring section                                 | : build in LCD display, or better                          |  |  |
|      |                 |           | PC communication interface                                    | : USB or Ethernet port, completed with communication cable |  |  |
|      |                 |           | Operating temperature   | : up to 50°C, or better                                    |  |  |
|      |                 |           | Power supply  | : single phase 230V, 50Hz                                  |  |  |
|      | II              |           |   | <b>U</b> 1,  |  |  |



## TECHNICAL SPECIFICATION DIVISION

Specification No.: RTES-115/2563 : AUTOMATIC INSULATION ANALYZER Page 6 of 8

### C3 Schedule of detailed requirement

|      | PEA      |          |  |                                    |  |  |
|------|----------|----------|--|------------------------------------|--|--|
| Item | Material | Quantity |  | •                                  | Description  |  |
|      | No.      |          |  |                                    |  |  |
|      |          |          | Co   | mplete with                        |  |  |
|      |          |          | 1.   | Power supply cord and plug         |  |  |
|      |          |          | 2.   | High-voltage supply shielded cab   | ole, not less than 18 meters long, with connecting               |  |
|      |          |          | 3.   | •                                  | ss than 18 meters long, with connection clamp                    |  |
|      |          |          | 4.   |                                    | r case for the analyzer and accessories                          |  |
|      |          |          | 5.   |                                    | ers long, with connection clamp and accessories                  |  |
|      |          |          | 6.   | Instruction and maintenance r      | manual, English, shall be contain following                      |  |
|      |          |          |  | information:                       |  |  |
|      |          |          |  | a) Operating principle             |  |  |
|      |          |          | b) Operating instruction of test set and user interface software |                                    |  |  |
|      |          |          | c) Setting and adjustments                                       |                                    |  |  |
|      |          |          |  | d) Maintenance instructions or tro | publeshooting instruction  |  |
|      |          |          |  | e) Part list and circuit diagram   |  |  |
|      |          |          | 7.   |                                    | useful function and using on computer wi                         |  |
|      |          |          |  | Windows operating system for       | analysis the data from the analyzer and marking                  |  |
|      |          |          |  | reports.                           |  |  |
|      |          |          | 8.   | Laptop computer, with:             |  |  |
|      |          |          |  | - Central Processing Unit (CPU)    | : intel core i5 up to 2.20 Ghz, or better                        |  |
|      |          |          |  | - Memory                           | : 8 GB DDR4, or better   |  |
|      |          |          |  | - Hard disk                        | : not less than 1 TB 5400 RPM + 128 GB SS                        |  |
|      |          |          |  | - Monitor                          | : 15 inch FHD, or better   |  |
|      |          |          |  | - Video memory                     | : not less than 4 GB GDDR5                                       |  |
|      |          |          |  | - Power supply                     | : single phase, 230V AC 50Hz and lithium ic rechargeable battery |  |
|      |          |          |  | - Operation system                 | : windows 7 with window license                                  |  |
|      |          |          |  | - Network connection               | : wi-fi, blue-tooth, lan, wireless lan                           |  |
|      |          |          |  | - Port and Interface               | : USB 2.0, USB 3.0 or better, and HDMI                           |  |
|      |          |          |  | - Laptop computer complete with    |  |  |
|      |          |          |  | 1) Microsoft office 2010 or lat    | ter edition with Microsoft license                               |  |
|      | II       |          |  | 2) Antivirus software (later ed    | lition) with product license                                     |  |



## TECHNICAL SPECIFICATION DIVISION

Specification No.: RTES-115/2563 : AUTOMATIC INSULATION ANALYZER Page 7 of 8

## C3 Schedule of detailed requirement

|      | PEA      |          |   |  |  |  |
|------|----------|----------|---|--|--|--|
| Item | Material | Quantity | Description   |  |  |  |
|      | No.      |          |   |  |  |  |
|      |          |          | 3) External optical mouse and mouse pad   |  |  |  |
|      |          |          | 4) Flash drive, capacity not less than 64 GB, USB 3.0, or better                      |  |  |  |
|      |          |          | 5) Carrying case  |  |  |  |
|      |          |          | 6) Power supply cord and plug   |  |  |  |
|      |          |          | 7) Other accessories according to manufacturer's design and auxiliary                 |  |  |  |
|      |          |          | equipment necessary to complete the functions   |  |  |  |
|      |          |          | 9. Other accessories according to manufacturer's design and auxiliary equipment       |  |  |  |
|      |          |          | necessary to complete the function  |  |  |  |
|      |          |          |   |  |  |  |
| 9    | -        | 1 lot    | Spare part for the automatic insulation analyzer in item 8 (give detail)              |  |  |  |
|      |          |          |   |  |  |  |
| 10   | -        | 1 lot    | Optional accessories for the automatic insulation analyzer in item 8 (give detail)    |  |  |  |
|      |          |          |   |  |  |  |
|      |          |          | Note:   |  |  |  |
|      |          |          | 1. The bidders shall be sole distributor or authorized representative and have a      |  |  |  |
|      |          |          | permanent office in Thailand; otherwise shall not be accepted.                        |  |  |  |
|      |          |          | 2. The bidders have to quote the unit costs.  |  |  |  |
|      |          |          | 3. The bidders have to quote spare parts and optional accessories with their lists of |  |  |  |
|      |          |          | quantities and itemized prices, if any. The prices of spare parts and optional        |  |  |  |
|      |          |          | accessories shall not be taken into consideration for the purpose of the bid          |  |  |  |
|      |          |          | evaluation; and PEA reserves the right to purchase some or all of items, to adjust    |  |  |  |
|      |          |          | their quantities, or to cancel them.  |  |  |  |
|      |          |          | 4. The bidders have to submit the automatic insulation analyzer for demonstration and |  |  |  |
|      |          |          | function checks within five (5) working days after the bid closing date; otherwise    |  |  |  |
|      |          |          | shall be rejected. The demonstration and function checks shall be done by the         |  |  |  |
|      |          |          | users, i.e. for automatic insulation analyzer the user in the central area is         |  |  |  |
|      |          |          | "Substation maintenance division", and shall be done at least following items:        |  |  |  |
|      |          |          | 4.1 Visual and/or dimension inspection  |  |  |  |
|      |          |          | 4.2 Function checks tests   |  |  |  |
|      |          |          | 4.3 Operation and/or installation tests   |  |  |  |
|      |          |          | 4.4 Other inspection/test according to users  |  |  |  |
|      | II       |          |   |  |  |  |



## TECHNICAL SPECIFICATION DIVISION

Specification No.: RTES-115/2563 : AUTOMATIC INSULATION ANALYZER Page 8 of 8

### C3 Schedule of detailed requirement

| Invitat | Invitation to Bid No.: |          |  |  |  |  |
|---------|------------------------|----------|--|--|--|--|
|         | PEA                    |          |  |  |  |  |
| Item    | Material               | Quantity | Description  |  |  |  |
|         | No.                    |          |  |  |  |  |
|         |                        |          | 5. Training course for operation and maintenance the proposed circuit breaker                    |  |  |  |
|         |                        |          | analyzer system shall be provided by the contractor for PEA's personal. The                      |  |  |  |
|         |                        |          | training shall not be less than three (3) days. The training shall be free of charge.            |  |  |  |
|         |                        |          | 6. The following automatic insulation analyzer products are proved to conform the specification; |  |  |  |
|         |                        |          | Item 5 - Megger/U.K. Model Trax 220  |  |  |  |
|         |                        |          | - Omicron/Austria Model CPC 100  |  |  |  |
|         |                        |          | Item 8 - Megger/U.K. Model Trax 220  |  |  |  |
|         |                        |          | - Omicron/Austria Model CPC 100  |  |  |  |
|         |                        |          | The demonstration and function check according to 4. Are not required for the above analyzer.    |  |  |  |
|         |                        |          | The other products can be proposed, but the bidders have to submit all technical document and    |  |  |  |
|         |                        |          | demonstration and function check according to 4. shall be submit for consideration.              |  |  |  |
|         |                        |          | 7. The bidder have to submitted the technical data of the automatic insulation analyzer          |  |  |  |
|         |                        |          | with the bid.  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         |                        |          |  |  |  |  |
|         | II                     |          |  |  |  |  |



## TECHNICAL SPECIFICATION DIVISION

Specification No.: RTES-115/2563 : AUTOMATIC INSULATION ANALYZER

Page 1 of 3

1

Invitation to Bid No.

C4 Price schedule

Manufacturer:

**Country of origin:** 

Trade-mark:

|      |                        |                  |   | Trade-mark: |   |  |
|------|------------------------|------------------|---|-------------|---|--|
| Item | PEA<br>Material<br>No. | Catalogue<br>No. | Description   | Quantity    | Unit Cost (See details & conditions attached) | Total Cost (See details & conditions attached) |
| 2    | -                      |                  | Portable insulation analyzer, for field testing of insulation in electrical equipment and apparatus up to 115 kV 50 Hz in live substations e.g. power transformers, bushings etc., and for measurements and calculations of capacitance, power factor, watt loss, current, and voltage; consisting of high voltage test section and control and measuring section  Spare parts for the portable insulation analyzer in item 1 (give detail)  2.1  2.2 | set(s)      |   |  |
| 3    | -                      |                  | 2.3 Optional accessories for the portable insulation analyzer in item 1 (give detail) 3.1 3.2 3.3   | 1 lot       |   |  |
| 4    | -<br>II                |                  | Training course for PEA's personnel including on-site training for operation and maintenance of the portable insulation analyzer in item 1.   | 1 lot       |   |  |



# TECHNICAL SPECIFICATION DIVISION

| Specification No.: RTES-115/2563 : AUTOMATIC INSULATION ANALYZER | Page 2 of 3 |
|--|-------------|
|--|-------------|

Invitation to Bid No.

C4 Price schedule

Manufacturer:

Country of origin:

|   |                        |                  |   | Trade-mark:          |  |  |
|---|------------------------|------------------|---|----------------------|--|--|
| Item                                    | PEA<br>Material<br>No. | Catalogue<br>No. | Description   | Quantity             | Unit Cost<br>(See details<br>& conditions<br>attached) | Total Cost (See details & conditions attached) |
| <ul><li>5</li><li>6</li><li>7</li></ul> | -                      |                  | Automatic insulation analyzer, fully automatic, modular and portable design, suitable for field testing of insulation in electrical equipment and apparatus up to 115 kV 50 Hz in live substations e.g. power transformers, circuit breakers, bushings etc., and for measurements and calculations of voltage, current, power factor, dissipation factor, capacitance, inductance, and watt loss; consisting of high voltage test section and control and measuring section Spare part for the automatic insulation analyzer in item 5 (give detail) 6.1 6.2 6.3 Optional accessories for the automatic insulation analyzer in item 5 (give detail) 7.1 7.2 7.3 | set(s)  1 lot  1 lot |  |  |
|   | II                     |                  |   |                      |  |  |



## TECHNICAL SPECIFICATION DIVISION

Specification No.: RTES-115/2563: AUTOMATIC INSULATION ANALYZER

Page 3 of 3

C4 Price schedule

Invitation to Bid No.

Country of origin:

Trade-mark:

Manufacturer:

|      |                        |                  |  | Trade-mark:          |   |  |
|------|------------------------|------------------|--|----------------------|---|--|
| Item | PEA<br>Material<br>No. | Catalogue<br>No. | Description  | Quantity             | Unit Cost (See details & conditions attached) | Total Cost (See details & conditions attached) |
| 9    | -                      |                  | Automatic insulation analyzer, fully automatic, modular and portable design, suitable for field testing of insulation in electrical equipment and apparatus e.g. transformer, circuit breakers, current transformer, voltage transformer, protection relay, etc., and for measurements and calculations of voltage, current and resistance; consisting of high voltage test section and control and measuring section  Spare part for the automatic insulation analyzer in item 8 (give detail)  9.1  9.2  9.3  Optional accessories for the automatic insulation analyzer in item 8 (give detail)  10.1  10.2  10.3 | set(s)  1 lot  1 lot |   |  |
|      | II                     |                  |  |                      |   |  |



### TECHNICAL SPECIFICATION DIVISION

### AUTOMATIC INSULATION ANALYZER

Specification No.: RTES-115/2563 | Approved date: 04/02/2563 | Rev. No.: - | Form No.: - | Page 1 of 9

## Technical data of the automatic insulation analyzer

### Item 1

| Description                                      | Unit | Proposed data |
|--|------|---------------|
| Manufacturer                                     | -    |               |
| Manufacturer's type/model                        | -    |               |
| Country of manufacturer                          | -    |               |
| Output voltage                                   | V    |               |
| Output current                                   | A    |               |
| Capacitance                                      | μF   |               |
| Power supply                                     | -    |               |
| Complete with                                    |      |               |
| 1. Input circuit-breaker                         | -    |               |
| 2. Standard protective device(s)                 | -    |               |
| 3. Automatic interference protection/suppression | -    |               |
| 4. Raise-lower voltage control                   | -    |               |
| 5. Resonating inductor for increases current     | -    |               |
| output (if any)                                  |      |               |
| 6. Indication and pilot lamps                    | -    |               |
| 7. Oil test cell, in accordance with ASTM-D 924  | -    |               |
| or equivalent; with case                         |      |               |
| 8. Main supply cord and plug                     | -    |               |
| 9. Shielded high-voltage test cable with pothead | -    |               |
| on both ends                                     |      |               |
| 10. Low-voltage test lead(s)                     | -    |               |
| 11. Safety ground leads and accessories          | -    |               |
| 12. Cable hook                                   | -    |               |
| 13. Instruction books                            | -    |               |



## TECHNICAL SPECIFICATION DIVISION

### AUTOMATIC INSULATION ANALYZER

Specification No.: RTES-115/2563 | Approved date: 04/02/2563 | Rev. No.: - | Form No.: - | Page 2 of 9

| Description                                       | Unit | Proposed data |
|---|------|---------------|
| 14. Other accessories according to manufacturer's | -    |               |
| design and auxiliary equipment not specified      |      |               |
| in these specifications, but necessary to         |      |               |
| complete the sound function                       |      |               |



## TECHNICAL SPECIFICATION DIVISION

### AUTOMATIC INSULATION ANALYZER

Specification No.: RTES-115/2563 | Approved date: 04/02/2563 | Rev. No.: - | Form No.: - | Page 3 of 9

### Item 5

| Description               | Unit | Proposed data |
|---------------------------|------|---------------|
| Manufacturer              | -    |               |
| Manufacturer's type/model | -    |               |
| Country of manufacturer   | -    |               |
| Safety standards          |      |               |
| - EMC                     | -    |               |
| - safety                  | -    |               |
| Function                  |      |               |
| - power transformer       | -    |               |
|                           |      |               |
|                           |      |               |
|                           |      |               |
|                           |      |               |
|                           |      |               |
|                           |      |               |
|                           |      |               |
|                           |      |               |
|                           |      |               |
| - current transformer     | -    |               |
|                           |      |               |
|                           |      |               |
|                           |      |               |
|                           |      |               |
| - voltage transformer     | -    |               |
|                           |      |               |
|                           |      |               |
|                           |      |               |



## TECHNICAL SPECIFICATION DIVISION

### AUTOMATIC INSULATION ANALYZER

Specification No.: RTES-115/2563 | Approved date: 04/02/2563 | Rev. No.: - | Form No.: - | Page 4 of 9

| Description                   | Unit | Proposed data |
|-------------------------------|------|---------------|
| Output voltage                |      |               |
| - AC voltage                  | V    |               |
| Output current                |      |               |
| - AC current                  | A    |               |
| - DC current                  | A    |               |
| Maximum output power          |      |               |
| - AC output power             | VA   |               |
| - DC output power             | VA   |               |
| Test voltage                  |      |               |
| - AC voltage range            | V    |               |
| - AC voltage accuracy         | -    |               |
| Test current                  |      |               |
| - AC current range            | A    |               |
| - DC current range            | A    |               |
| - AC current accuracy         | -    |               |
| - DC current accuracy         | -    |               |
| Test frequency                |      |               |
| - AC frequency range          | Hz   |               |
| Power factor                  |      |               |
| - power factor range          | -    |               |
| - power factor accuracy       | -    |               |
| Dissipation factor            |      |               |
| - dissipation factor range    | %    |               |
| - dissipation factor accuracy | -    |               |
| Capacitance (at 50 Hz)        |      |               |
| - capacitance range           | μF   |               |
| - capacitance accuracy        | -    |               |



## TECHNICAL SPECIFICATION DIVISION

### AUTOMATIC INSULATION ANALYZER

Specification No.: RTES-115/2563 Approved date: 04/02/2563 Rev. No.: - Form No.: - Page 5 of 9

| Description  | Unit | Proposed data |
|--|------|---------------|
| Inductance (at 50 Hz)                                    |      |               |
| - inductance range                                       | Н    |               |
| - inductance accuracy                                    | -    |               |
| Control and measuring section                            | -    |               |
| PC communication interface                               | -    |               |
| Operating temperature                                    | -    |               |
| Power supply   | -    |               |
| Complete with  |      |               |
| 1. Serial interface for a accessories device such as tan | -    |               |
| delta unit   |      |               |
| 2. Instruction and maintenance manual, English,          | -    |               |
| shall be contain following information:                  |      |               |
| a) Operating principle                                   |      |               |
| b) Operating instruction of test set and user            |      |               |
| interface software                                       |      |               |
| c) Setting and adjustments                               |      |               |
| d) Maintenance instructions or troubleshooting           |      |               |
| instruction  |      |               |
| e) Part list and circuit diagram                         |      |               |
|  |      |               |
| 3. High-voltage supply shielded cable, not less than     | -    |               |
| 18 meters long, with connection clamp                    |      |               |
| 4. Measuring shielded cables, , not less than 18         | -    |               |
| meters long, with connection clamps                      |      |               |
| 5. Grounding cable, not less than 6 meters long, with    | -    |               |
| connection clamp and accessories                         |      |               |
| 6. Power supply and plug                                 | -    |               |



### TECHNICAL SPECIFICATION DIVISION

### AUTOMATIC INSULATION ANALYZER

Specification No.: RTES-115/2563 | Approved date: 04/02/2563 | Rev. No.: - | Form No.: - | Page 6 of 9

|     | Description  | Unit | Proposed data |
|-----|--|------|---------------|
| 7.  | Thermometer and hygrometer for measuring air           | -    |               |
|     | temperature and humidity                               |      |               |
| 8.  | Transport cart and carrying bag or case for the        | -    |               |
|     | analyzer and accessories                               |      |               |
| 9.  | Oil test cell, in accordance with ASTM D924, or        | -    |               |
|     | equivalent with carrying case                          |      |               |
| 10. | Software package comprising useful function and        | -    |               |
|     | using on computer with Windows <sup>TM</sup> operating |      |               |
|     | system for analysis the data from the analyzer         |      |               |
|     | and marking reports.                                   |      |               |
| 11. | Certificate of calibration                             | -    |               |
| 12. | Switchbox  | -    |               |
| 13. | Other accessories according to manufacturer's design   | -    |               |
|     | and auxiliary equipment necessary to complete the      |      |               |
|     | function   |      |               |



## TECHNICAL SPECIFICATION DIVISION

### AUTOMATIC INSULATION ANALYZER

Specification No.: RTES-115/2563 | Approved date: 04/02/2563 | Rev. No.: - | Form No.: - | Page 7 of 9

### Item 8

| Description                   | Unit | Proposed data |
|-------------------------------|------|---------------|
| Manufacturer                  | -    |               |
| Manufacturer's type/model     | -    |               |
| Country of manufacturer       | -    |               |
| Safety standards              |      |               |
| - EMC                         | -    |               |
| - safety                      | -    |               |
| Output voltage                |      |               |
| - AC voltage                  | V    |               |
| Output current                |      |               |
| - AC current                  | A    |               |
| - DC current                  | A    |               |
| Maximum output power          |      |               |
| - AC output power             | VA   |               |
| - DC output power             | VA   |               |
| Test voltage                  |      |               |
| - AC voltage range            | V    |               |
| - AC voltage accuracy         | -    |               |
| Test current                  |      |               |
| - AC current range            | A    |               |
| - DC current range            | A    |               |
| - AC current accuracy         | -    |               |
| - DC current accuracy         | -    |               |
| Test frequency                |      |               |
| - AC frequency range          | Hz   |               |
| Control and measuring section | -    |               |
| PC communication interface    | -    |               |



## TECHNICAL SPECIFICATION DIVISION

### AUTOMATIC INSULATION ANALYZER

Specification No.: RTES-115/2563 | Approved date: 04/02/2563 | Rev. No.: - | Form No.: - | Page 8 of 9

| Description  | Unit | Proposed data |
|--|------|---------------|
| Operating temperature                                | -    |               |
| Power supply   | -    |               |
| Complete with  |      |               |
| Power supply cord and plug                           | -    |               |
| 2. High-voltage supply shielded cable, not less than | -    |               |
| 18 meters long, with connecting clamp                |      |               |
| 3. Measuring shielded cables, not less than 18       | -    |               |
| meters long, with connection clamp                   |      |               |
| 4. Transport cart and carrying bag or case for the   | -    |               |
| analyzer and accessories                             |      |               |
| 5. Ground cable, not less than 6 meters long, with   | -    |               |
| connection clamp and accessories                     |      |               |
| 6. Instruction and maintenance manual in English and | -    |               |
| maintenance manual, English, shall be contain        |      |               |
| following information:                               |      |               |
| a) Operating principle                               |      |               |
| b) Operating instruction of test set and user        |      |               |
| interface software                                   |      |               |
| c) Setting and adjustments                           |      |               |
| d) Maintenance instructions or troubleshooting       |      |               |
| instruction  |      |               |
| e) Part list and circuit diagram                     |      |               |
| 7. Software package comprising useful function and   | -    |               |
| using on computer with Windows TM operating          |      |               |
| system for analysis the data from the analyzer       |      |               |
| and marking reports.                                 |      |               |



## TECHNICAL SPECIFICATION DIVISION

### AUTOMATIC INSULATION ANALYZER

Specification No.: RTES-115/2563 | Approved date: 04/02/2563 | Rev. No.: - | Form No.: - | Page 9 of 9

|    | Description  | Unit | Proposed data |
|----|--|------|---------------|
| 8. | Laptop computer, with:                             |      |               |
|    | - Central Processing Unit (CPU)                    | -    |               |
|    | - Memory   |      |               |
|    | - Hard disk  |      |               |
|    | - Monitor  |      |               |
|    | - Video memory                                     |      |               |
|    | - Power supply                                     |      |               |
|    | - Weight   |      |               |
|    | - Operation system                                 |      |               |
|    | - Network connection                               |      |               |
|    | - Port and Interface                               |      |               |
|    | - Laptop computer complete with                    |      |               |
|    | 1) Microsoft office 2010 or later edition with     |      |               |
|    | Microsoft license                                  |      |               |
|    | 2) Antivirus software (later edition) with product |      |               |
|    | license  |      |               |
|    | 3) External optical mouse and mouse pad            |      |               |
|    | 4) Flash drive, capacity not less than 64 GB,      |      |               |
|    | USB 3.0, or better                                 |      |               |
|    | 5) Carrying case                                   |      |               |
|    | 6) Power supply cord and plug                      |      |               |
|    | 7) Other accessories according to manufacturer's   |      |               |
|    | design and auxiliary equipment necessary to        |      |               |
|    | complete the functions                             |      |               |
| 9. | Other accessories according to manufacturer's      | -    |               |
|    | design and auxiliary equipment necessary to        |      |               |
|    | complete the function                              |      |               |